



STOPS RUST® ENAMEL SPRAYS

DESCRIPTION AND USES

Rust-Oleum® Stops Rust® Enamel Sprays are designed to provide a durable protective coating with excellent rust prevention, and excellent resistance to abrasion, fading, chipping, and dulling. These sprays apply easily, provide excellent coverage and dry fast to a tough attractive finish. Rust-Oleum Stops Rust Enamel Sprays are ideal for ferrous, non-ferrous metal and wood surfaces. It features a comfort tip with a wider finger pad to reduce fatigue caused by continuous spraying and an any-angle tip which allows you to spray at any angle. Not for use on galvanized metal.

PRODUCTS

SKU	DESCRIPTION (12 Ounce Aerosol)
7721830	Fresh Blue
7722830	Harbor Blue
7723830	Navy
7724830	Sail Blue
7727830	Royal Blue
7731830	Grass Green
7733830	Dark Hunter Green
7738830	Hunter Green
7747830	Sunburst Yellow
7754830	Anodized Bronze
7762830	Sunrise Red
7763830	Carnival Red
7765830	Regal Red
7768830	Burgundy
7770830	Almond
7771830	Sand
7775830	Leather Brown
7776830	Flat Black
7779830	Gloss Black
7783830	Pewter Gray
7784830	Charcoal Gray
7786830	Smoke Gray
7789830	Canvas White
7790830	Flat White
7792830	Gloss White
7794830	Antique White
7797830	Semi-Gloss White
7798830	Semi-Gloss Black
214804	Orange
214085	Flat Brown
214086	Charleston Green
214087	Army Green
241235	Pistachio
241236	Glacier Blue

PRODUCTS (cont.)

SKU	DESCRIPTION (12 Ounce Aerosol)
245897	Burnt Orange
248567	Merlot
248568	Cherry
248569	Emerald
248630	French Roast
248631	Night Tide
249032	Khaki
250702	Pure White
250703	Cobblestone
250704	Lobster Red
250705	Fern
262661	Dark Walnut
267112	Kona Brown
269292	Maui Blue
277239	Lagoon
284678	Gloss Light Turquoise
298537	Gloss Tuscan Sun
312816	Gloss Rich Jade
312817	Gloss Cambridge Stone
312818	Gloss Deep Slate
312821	Flat Red Rock

PRODUCT APPLICATION

Use outdoors or in a well-ventilated area such as an open garage. Use when temperature is between 50°-90°F (10°-32°C) and humidity is below 70% to ensure proper drying. Do not apply to surfaces that, when heated, exceed 200°F (93°C) or galvanized metal. Avoid spraying in very windy, dusty conditions. Cover surrounding area to protect from spray mist.

SURFACE PREPARATION

Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with a commercial detergent, or other suitable cleaning method. Rinse with fresh water and allow to thoroughly dry. Remove loose paint and rust with a wire brush or sandpaper. Previously coated surfaces must be sound and in good condition. Smooth, hard, or glossy finishes should be scarified by sanding to create a surface profile.

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead paint dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE; ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.



**STOPS RUST®
ENAMEL SPRAYS**

PRODUCT APPLICATION (cont.)

PRIMING

Use of a Stops Rust® Primer provides added corrosion protection, superior adhesion and hiding and is especially recommended for bare wood and metal. The following primers are recommended.

- 7769 Rusty Metal Primer
- 7780 Clean Metal Primer
- 2081 Light Gray Auto Primer
- 2067 Red Auto Primer
- 2089 Dark Gray Auto Primer

APPLICATION

Shake can vigorously for one minute after mixing ball begins to rattle. If mixing ball fails to rattle DO NOT STRIKE CAN. Contact Rust-Oleum. Shake often during use. Hold can upright 10-16" from surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface. Keep the can in motion while spraying. Apply 2 or more light coats a few minutes apart to avoid runs and sags. Do not use near open flame.

DRY AND RECOAT TIMES

Based on 70°F (21°C) 50% relative humidity. Allow more time at cooler temperatures. Dries tack free in 2-4 hours, to handle in 5-9 hours and fully dry in 24 hours. Primers may be top coated immediately. Apply a second coat or clear coat within 1 hour or after 48 hours.

PRODUCT APPLICATION (cont.)

CLEAN UP

Wipe off tip before storing. Clean up wet paint with Xylene or mineral spirits. Throw away empty can in trash pickup. Do not burn or place in home trash compactor.

CLOGGING

If valve clogs, twist and pull off spray tip and rinse it in a solvent such as mineral spirits. Do not stick a pin or other objects into the stem.

	TECHNICAL DATA	SRT-01
STOPS RUST® ENAMEL SPRAYS		

PHYSICAL PROPERTIES

		ENAMEL SPRAY FINISHES
Resin Type		Oil modified Alkyd
Pigment Type		Varies with color
Solvents		Acetone, N-Butyl Acetate, Aromatic Hydrocarbons
MIR		0.95 Max
Fill Weight		12 ounces
Recommended Dry Film Thickness (DFT) Per Coat		1.0-2.0 mils (25-50µ)
Practical Coverage at Recommended DFT (assumes 15% material loss)		6-10 sq.ft./can (0.6-0.9 m ² /can)
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity	Touch	2-4 hours
	Handle	5-9 hours
	Recoat	Before 1 hour or after 48 hours
Dry Heat Resistance		200°F (93°C)
Shelf Life		5 years
Flash Point		156°F (69°C)
Safety Information		For additional information, see SDS

Calculated values are shown and may vary from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, Illinois 60061

Phone: 877-385-8155
www.rustoleum.com

Form: GDH-678
Rev.: 092118